

### Product information

This product is not suitable for use as a standalone termite management system for an entire structure. HomeGuard sheeting products (DPC, Blue and TMB) when used in conjunction with HomeGuard Collars and HomeGuard GT are intended for use as a complete Termite Management System.

### Application

Cut cartridge tip, pierce foil membrane inside base of thread. Cut the nozzle end to the required opening diameter (4-6mm) at the desired angle (approx. 45 degrees). Fit to the top of the cartridge.

Drying Time; Skins immediately, maximum toughness achieved over several days.

Clean Up; Turps. Remove dried sealant from skin by gently rubbing with petroleum jelly.

Notes: \*may damage some plastics e.g. polystyrene, polycarbonate. Not for permanent water emersion. When cold, store at room temperature for easier use.

### Storage and Disposal

Store in closed original packaging, in a cool, well ventilated area away from children, animals, food and feedstuffs. Do not store for prolonged periods in direct sunlight. Do NOT allow product to enter sewers, drains, creeks or any other waterways.

### Protection of Wildlife, Fish, Crustacean and the Environment

Do not contaminate dams, rivers, streams, waterways or drains with product or the used container. Do not use in or around fishponds.

### Protection of Pets and Livestock

Before applying, remove animals and pets from the areas to be treated. Ensure that treated areas are never accessible to pets or livestock.

**First Aid** If poisoning occurs, contact a doctor or Poisons Information Centre. Phone Australia 13 11 26. If swallowed DO NOT induce vomiting. In case of eye contact flush eyes with copious quantities of water for at least 15 minutes. Seek medical advice.

### Material Safety Data Sheet

Additional information is listed in the Material Safety Data Sheet.

**Warning** Avoid repeated exposure or prolonged skin contact. Use in well ventilated area. Intentional misuse by deliberately inhaling the vapours from this product can be harmful or fatal. Highly flammable vapours can be ignited by flame or spark. This product has been classified as hazardous according to the criteria of NOHSC and HSN0. Please consult the material data sheet for more information. 24hr Emergency Response Number Toll Free Australia 1800 033 111 & New Zealand 0800 734 607.


### WARRANTY

FMC makes no warranty expressed or implied, concerning the use of this product other than that indicated on the label. Except as so warranted the product is sold as is. Buyer and user assume all risk of use and/or handling and/or storage of this material when such use and/or handling and/or storage is contrary to label instructions.



FMC Australasia Pty Ltd  
26/8 Metroplex Ave  
Murarrie Qld 4172  
Contact Number 1800 066 355

© FMC and HomeGuard are Registered Trademarks of FMC Corporation, Philadelphia, USA



### TERMITICIDAL ADHESIVE & SEALANT

Active constituent 2g/kg bifenthrin

**GROUP 3A INSECTICIDE**

**Termiticidal Adhesive and Sealant to be used in conjunction with components of HomeGuard™ for Precision Termite Management**

Only to be used by HomeGuard accredited personnel

## Contents: 260g

### HomeGuard Termiflex – Termiticidal Adhesive and Sealant:

### DIRECTIONS FOR USE (All states except TAS)

#### Restraints:

Do not use for remedial treatment of pre-existing termite infestations

Pest	Situations	Rate	Critical Comments
Subterranean termites	Domestic, commercial, and industrial structures - approved to be used in conjunction with HomeGuard sheet products to form a bond to join sheets together. Also to adhere HomeGuard sheet products to other structural components (eg. timber, concrete, tiles, steel etc). Can be used in various situations where by a Termiticidal sealant/adhesive will assist in the prevention of concealed termite entry into a structure.	A single continuous bead applied between two surfaces will create a bond (and/or seal) with Termiticidal activity when used in accordance with product instructions.	Application of the adhesive/sealant as per the below steps can assist in the management of termites by preventing termites passing through a gap completely and continuously sealed using this product. <ol style="list-style-type: none"><li>1. Surface must be clean, dry, free from dust, loose particles and soap residues. If required clean with turps.</li><li>2. Cut cartridge tip at 45 degrees approximately 4-6mm in diameter</li><li>3. Apply firmly onto surface or into joint by pushing sealant ahead of nozzle.</li><li>4. If necessary, smooth sealant immediately with tool dipped in turps.</li></ol> Refer to the HomeGuard Product Manual for further installation instructions.

**NOT TO BE USED FOR ANY PURPOSE, OR IN ANY MANNER, CONTRARY TO THIS LABEL UNLESS AUTHORISED UNDER APPROPRIATE LEGISLATION.**

### General Instructions

Insecticide Resistance Warning

**GROUP 3A INSECTICIDE**

For insecticide resistance management Termiflex is a Group 3A insecticide. Some naturally occurring insect biotypes resistant to Termiflex and other Group 3A insecticides may exist through normal genetic variability in any insect population. The resistant individuals can eventually dominate the insect population if Termiflex or other 3A insecticides are used repeatedly. The effectiveness of Termiflex on resistant individuals could be significantly reduced. Since occurrence of resistant individuals is difficult to detect prior to use, FMC Australasia Pty Ltd accepts no liability for any losses that may result from the failure of Termiflex to control resistant insects. Termiflex may be subject to specific resistance management strategies. For further information contact your local supplier or FMC Australasia Pty Ltd representative or local agricultural department agronomist.

Batch Number:

Date of Manufacture:

05-552